SANGHA Finishes

ARCHITECHTURAL SPECIFICATIONS FOR PLASTER AND BOUTIQUE FINISHES

- Coordinate related sections to ensure satisfactory preparation of substrates. Because Natural Plasters and other Artisan Finishes are applied in thin coats, some irregularities in substrates may telegraph through the finished surface. Use care when specifying substrates to define acceptable levels of quality adequately.

- Finishes applied by SANGHA can be installed over most types of smooth plaster substrates, including two and three-coat gypsum plaster systems, joint compound, and gypsum veneer plaster. The substrate must have a smooth steel trowel finish or equivalent.

- Specify expansion and control joints, corner beads, flashings, and required trim. Require corrosion-resistant trim and fasteners in wet areas.

- SANGHA Finishes can also be used over other select smooth, prime-painted interior substrates. Contact SANGHA Finishes for substrate preparation recommendations.

- Gypsum Drywall: Provide level 4 or higher finish in accordance with Gypsum Association's GA-214 – Recommended Levels of Gypsum Board Finish; Level 5 provides the highest quality and is especially recommended where severe lighting conditions occur, on large wall areas, and when smooth, gloss finishes are desired. Surfaces must be primed with Kilz 2 or another primer approved by SANGHA Finishes. (No PVA primer.)